

# THERMOFLEX / DUOFLEX

Radial / axial flexible Einweg-Färbehülsen.

Radially / axially flexible one-way dyetubes.

Tubes de teinture perdus, radialement / axialement flexible.



Art.Nr.	Typ	d <sub>1</sub> (mm)	d <sub>2</sub> (mm)	D <sub>3</sub> (mm)	D <sub>4</sub> (mm)	L (mm)	V <sub>max</sub> (mm)	V <sub>min</sub> (mm)	P (mm)	s (mm)	T (mm)	G (g)
2323	THERMOFLEX* / 33.0	59.00	54.00	67.00	67.00	170.0	161.5	-	143.0	3.50	8.5	45.0
2375	THERMOFLEX	59.00	54.00	67.00	67.00	170.0	161.5	-	143.0	3.50	8.5	40.0
2312	THERMOFLEX	56.00	46.00	60.00	60.00	230.0	219.5	-	186.0	3.50	10.5	51.0
2393	DUOFLEX* / 30.5	69.20	57.80	75.00	75.00	290.0	278.0	-	243.0	3.50	12.0	110.0
2396	DUOFLEX	69.20	57.80	75.00	75.00	290.0	278.0	-	243.0	3.50	12.0	104.0

Art.Nr.	Typ	D <sub>Z</sub> (mm)	d <sub>1</sub> (mm)	d <sub>2</sub> (mm)	D <sub>3</sub> (mm)	D <sub>4</sub> (mm)	L (mm)	V <sub>max</sub> (mm)	V <sub>min</sub> (mm)	P (mm)	s (mm)	T (mm)	G (g)
1381	COMBIFLEX* / 33		60.00	54.00	66.00	69.00	170.0	161.0	116.0	152.0	6.00	9.0	60.0

Art.Nr.	Typ	D <sub>Z</sub> (mm)	d <sub>1</sub> (mm)	d <sub>2</sub> (mm)	D <sub>3</sub> (mm)	D <sub>4</sub> (mm)	L (mm)	V <sub>max</sub> (mm)	V <sub>min</sub> (mm)	P (mm)	s (mm)	T (mm)	G (g)
1355	THERMO / 55.5		63.00	63.00	67.60	67.00	174.0	-	-	152.0	2.00	-	60.0
1359	THERMO / 57		65.00	65.00	69.60	69.00	230.0	-	-	197.6	2.00	-	84.0
1357	THERMO / 57		83.00	83.00	88.70	88.10	290.0	-	-	249.6	2.20	-	144.0

Art.Nr.	Typ	Kon	d <sub>1</sub> (mm)	d <sub>2</sub> (mm)	D <sub>3</sub> (mm)	D <sub>4</sub> (mm)	L (mm)	V <sub>max</sub> (mm)	V <sub>min</sub> (mm)	P (mm)	s (mm)	T (mm)	G (g)
1213	THERMO / 4° 20'		58.50	33.00	36.20	61.70	170.0	-	-	140.0	1.60	-	35.0
1214	THERMO / 4° 20'		55.00	33.00	37.00	59.00	145.0	-	-	119.0	2.00	-	30.0

\*) Zentrier-Ring 33mm • centering ring 33mm • anneau de centrage 33mm

